

## CARELLA

#### **DECORATIVE 360 ° CANDLE EFFECT SPIKE LIGHT**

#### LUMINAIRE REF:

PROJECT REF:


The Carella, a decorative outdoor garden candle light, is ideal for use in the garden and produces a 360 atmospheric light whilst being used to discreetly light foliage and low level planting whilst creating a glowing candle effect.

The Carella outdoor garden candle light looks great when placed in groups, for example a cluster of three in an area of planting. It also looks wonderful along a path to light your way and is a versatile fitting being suitable for modern contemporary town houses as well as traditional country houses. Independently tested by the LIA.



ALUMINIUM

BRONZE





360

#### ACCESSORIES



**IP66 ENCLOSURE** FOR DRIVER LARGE ACENIPLRG

**IP66 ENCLOSURE** FOR DRIVER SMALL ACENIPSML



IP68 IN-LINE CONNECTION ACILIP68C



CONNECTION ACYJBIP68



UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

© John Cullen Lighting 2024. Technical data figures are for guidance only and are subject to ±5% tolerance We reserve the right to change the design and specification of our product range without prior notice. E&OE



WWW.JOHNCULLENLIGHTING.COM

# II EN

### CARELLA DECORATIVE 360 ° CANDLE EFFECT SPIKE LIGHT

360

360°

N/A


360°

SPECIFICATION

BEAM ANGLE (°)

LUMINAIRE REF:


PROJECT REF:



COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	>90 Ra
1-30 COLOUR FIDELITY (Rf)	N/A
M-30 COLOUR GAMUT (Rg)	>95
BINNING	2 SDCM
IFETIME L70/B10 (HOURS)	>50000
1BIENT TEMPERATURE (Ta)	-20 +40 °C
OTHER DATA	
CABLE TYPE	2 Core Silicone (180 °C)
CABLE SIZE	6.4mm OD - 2 off 24/0.2 (0.75mm2)

WEIGHT 240g FIRE RATED N/A

LED SOURCE LUMENS (LM)	72 lm	72 lm	120*	$X \rightarrow X \setminus$
LUMINAIRE LUMENS (LM)	24.3 lm	24.3 lm		
INTENSITY RATING (CD)	N/A	N/A		
POWER CONSUMPTION (W)	1W	1W	90°	
LUMINAIRE EFFICACY (LM/W)	24.3 lm/W	24.3 lm/W	A0.	
DRIVE CURRENT (mA)	350mA	350mA		
FORWARD VOLTAGE (V DC)	2.8V DC	2.8V DC		
			60°	X + X /
				$X \rightarrow X$
			C0 / C180	r° 0° 30° cd / 1000 lm
INGRESS RATIN	IC ID45		COLOUR TEMPERATURE	27004
IMPACT RATIN			CIE CRI AVAILABLE AS	
		045		
COMPLIANC	CE IEC/EN 60598-1:2		IES TM-30 COLOUR FIDELITY (Rf)	
	IEC/EN 60598-2-7	:1997	IES TM-30 COLOUR GAMUT (Rg)	
			BINNING	
			LIFETIME L70/B10 (HOURS)	>50000
			AMBIENT TEMPERATURE (Ta)	-20 +40 °C
ELECTRICA			OTHER DATA	
SOURCE TYP	PE LED		CABLE TYPE	2 Core Silicone (180 °C)
PRODUCT CLAS	SS Class III (SELV low	voltage)	CABLE SIZE	6.4mm OD - 2 off 24/0.2 (0.75mm2)
DIMMING PROTOCO	DL DALI dimmable		CABLE LENGTH	4600mm
	1-10V dimmable		CONNECTOR TYPE	N/A



Switched



## 3 WARRANTY

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

© John Cullen Lighting 2024. Technical data figures are for guidance only and are subject to ±5% tolerance We reserve the right to change the design and specification of our product range without prior notice. E&OE



WWW.JOHNCULLENLIGHTING.COM