

KEW 40 SURFACE

GLK4WN062

LUMINAIRE REF:


PROJECT REF:



BRONZE

DIRECTIONAL BRONZE NARROW WALL MOUNTED SPOTLIGHT

The Kew 40 Surface is a surface mounted IP66 spotlight, ideal for pinpointing landscape ornaments from above or wall grazing for use both inside and out. Our unique, patented wall mounting system allows for quick, tool-free installation on site. The luminaire mounts onto the wall bracket and is self-locking at 15° intervals, preventing the need for further fixing. A discreet, optional tamper proofing feature is available if required for commercial projects. Independently tested by the LIA.



NARROW

ACCESSORIES



IP66 ENCLOSURE  
FOR DRIVER  
LARGE  
ACENIPLRG



IP66 ENCLOSURE  
FOR DRIVER  
SMALL  
ACENIPSML



KEW/HAMPTON  
40 CONDUIT BOX  
ACHK4CB1



KEW 40 CAP  
SNOOT BRONZE  
ACK4CS061



KEW 40 FULL  
SNOOT BRONZE  
ACK4FS061



KEW 40 HALF  
SNOOT BRONZE  
ACK4HS061



KEW 40 SHORT  
SNOOT BRONZE  
ACK4SS061



WWW.JOHN CULLEN LIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81




KEW 40 SURFACE  
GLK4WN062

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	NARROW
BEAM ANGLE (°)	18°
LED SOURCE LUMENS (LM)	840 lm
LUMINAIRE LUMENS (LM)	572 lm
INTENSITY RATING (CD)	4451
POWER CONSUMPTION (W)	8W
LUMINAIRE EFFICACY (LM/W)	71.5 lm/W
DRIVE CURRENT (mA)	700mA
FORWARD VOLTAGE (V DC)	12V



INGRESS RATING	IP66
IMPACT RATING	N/A
COMPLIANCE	

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	>94 Ra
IES TM-30 COLOUR FIDELITY (Rf)	>90
IES TM-30 COLOUR GAMUT (Rg)	N/A
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 ... +40 °C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	DALI dimmable
	1-10V dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	2 Core Silicone (180 °C)
CABLE SIZE	6.4mm OD - 2 off 24/0.2 (0.75mm <sup>2</sup> )
CABLE LENGTH	350mm
CONNECTOR TYPE	N/A
WEIGHT	275g
FIRE RATED	N/A

