

VORSA FIX 30 BLACK MEDIUM 2700K
SLVF3M021

LUMINAIRE REF:

PROJECT REF:




BLACK RAL 9005

FIXED MOUNTED DIRECTIONAL SPOTLIGHT

The Vorsa Fix 30 spotlight is a versatile mini surface-mounted directional spotlight. This fitting is ideal for use in areas such as living areas, hallways, kitchens, and dining rooms, as well as other key areas of the home. It is perfect for use on beams and concrete ceilings where recessed fittings are unsuitable.

This relatively small spotlight is discreet and easy to direct the light to where required. The fitting has a deep baffle which ensures that glare is minimised. Independently tested by the LIA.



MEDIUM

ACCESSORIES



VORSA 30
HONEYCOMB
INSERT Ø27.5MM
ACHCVO301



VORSA 30 LINEAR
SPREADER LENS
Ø27.5MM
ACLLVO301



VORSA 30 SAND
BLASTED GLASS
LENS Ø27.5MM
ACSGVO301



VORSA 30 HIGH
TRANSMISSION
SOFTENING LENS
Ø27.5MM
ACSLVO301





VORSA FIX 30 BLACK MEDIUM 2700K
SLVF3M021

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	MEDIUM
BEAM ANGLE (°)	25°
LED SOURCE LUMENS (LM)	400
LUMINAIRE LUMENS (LM)	325
INTENSITY RATING (CD)	1540
POWER CONSUMPTION (W)	3.9
LUMINAIRE EFFICACY (LM/W)	83
DRIVE CURRENT (mA)	350
FORWARD VOLTAGE (V DC)	N/A

INGRESS RATING	IP20
IMPACT RATING	IK03
COMPLIANCE	IEC/EN 60598-1:2015

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	>90 Ra
IES TM-30 COLOUR FIDELITY (Rf)	90
IES TM-30 COLOUR GAMUT (Rg)	>95
BINNING	1/16th ANSI 1931 CIE
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 ... +35 °C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	1-10V dimmable
	DALI dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	2 Core PTFE (200 °C)
CABLE SIZE	2 off 7/0.2 (0.22mm2)
CABLE LENGTH	300mm
CONNECTOR TYPE	Leads included
WEIGHT	N/A
FIRE RATED	N/A



WWW.JOHN CULLENLIGHTING.COM
UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

