

TUNE 50 NARROW 2700 - 6500K
LETU50NA2765121



LUMINAIRE REF:

PROJECT REF:



N/A

TAKE CONTROL WITH TUNABLE LIGHTING FOR YOUR PERFECT MIX OF BRIGHTNESS AND WARMTH
Take control for your perfect mix of brightness and warmth with our Tune 50 Engine. Designed in Britain, the Tune 50 offers a range of CCTs from 2700K up to 6500K.



NARROW





TUNE 50 NARROW 2700 - 6500K
LETU50NA2765121

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	NARROW
BEAM ANGLE (°)	20°
LED SOURCE LUMENS (LM)	866 lm @ 2700K
LUMINAIRE LUMENS (LM)	N/A
INTENSITY RATING (CD)	4913
POWER CONSUMPTION (W)	12W
LUMINAIRE EFFICACY (LM/W)	50 lm/W
DRIVE CURRENT (mA)	350mA
FORWARD VOLTAGE (V DC)	36V DC

INGRESS RATING	IP20
IMPACT RATING	N/A
COMPLIANCE	IEC/EN 62031:2020

COLOUR TEMPERATURE	2700K - 6500K
CIE CRI AVAILABLE AS	>95 Ra
IES TM-30 COLOUR FIDELITY (Rf)	N/A
IES TM-30 COLOUR GAMUT (Rg)	N/A
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	Please check the data sheet of the intended product to use with

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	DALI dimmable
	1-10V dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	Silicone
CABLE SIZE	4 off 18AWG
CABLE LENGTH	125mm
CONNECTOR TYPE	N/A
WEIGHT	N/A
FIRE RATED	N/A



WWW.JOHN CULLEN LIGHTING.COM
UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

