

ETTA CABINET LIGHT
RECESSED TASK AND DISPLAY LIGHT


LUMINAIRE REF:

PROJECT REF:



The Etta is a precision engineered LED under cabinet light that can also be used for recessed task and display lighting. It is suitable for under shelf lighting, bespoke cabinetry, kitchens and marine lighting. Can be used to create continuous light onto a work surface under a kitchen cabinet. It is now available in both 2700K and 2400K to suit your interiors.

The Etta under cabinet light is also available with an eyelid to minimise glare - see Etta Eyelid.



ALUMINIUM



BRONZE



WHITE RAL 9910



WIDE WASH

ACCESSORIES



SURFACE MOUNT
COLLAR WHITE
ACUCSM012



SURFACE MOUNT
COLLAR BRONZE
ACUCSM062



SURFACE MOUNT
COLLAR
ALUMINIUM
ACUCSM102




ETTA CABINET LIGHT
RECESSED TASK AND DISPLAY LIGHT

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	WIDE WASH
BEAM ANGLE (°)	90°
LED SOURCE LUMENS (LM)	330 lm
LUMINAIRE LUMENS (LM)	280 lm
INTENSITY RATING (CD)	130
POWER CONSUMPTION (W)	3W
LUMINAIRE EFFICACY (LM/W)	93 lm/W
DRIVE CURRENT (mA)	350mA
FORWARD VOLTAGE (V DC)	8.5V DC



INGRESS RATING	IP54
IMPACT RATING	IK02
COMPLIANCE	IEC/EN 60598-1:2015
	IEC/EN 60598-2-2:2012

COLOUR TEMPERATURE	2400K / 2700K
CIE CRI AVAILABLE AS	>90 Ra (2400K) / >95 (2700K)
IES TM-30 COLOUR FIDELITY (Rf)	>90 (2400K) / >95 (2700K)
IES TM-30 COLOUR GAMUT (Rg)	>95
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 ... +35 °C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	DALI dimmable
	1-10V dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	2 Core PVC (80 °C)
CABLE SIZE	2 off 22 AWG 7/30 (0.33mm2) Copper Strands
CABLE LENGTH	2000mm
CONNECTOR TYPE	N/A
WEIGHT	35g
FIRE RATED	N/A

