

ETTA BRONZE 2700K

SCFU27063

LUMINAIRE REF:

PROJECT REF:




BRONZE

RECESSED TASK AND DISPLAY BRONZE LIGHT

The Etta is a precision engineered LED under cabinet light that can also be used for recessed task and display $lighting. \ It is suitable for under shelf lighting, be spoke cabinetry, kitchens and marine lighting. \ Can be used to create$ continuous light onto a work surface under a kitchen cabinet. It is now available in both 2700K and 2400K to suit your interiors.

The Etta under cabinet light is also available with an eyelid to minimise glare - see Etta Eyelid. Independently tested by the Eurofins.



30/04/2024 V1.127



WIDE WASH

ACCESSORIES



COLLAR WHITE









SURFACE MOUNT COLLAR ALUMINIUM ACUCSM102



WWW.JOHNCULLENLIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81








ETTA BRONZE 2700K

SCFU27063

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	WIDE WASH
BEAM ANGLE (°)	90°
LED SOURCE LUMENS (LM)	330 lm
LUMINAIRE LUMENS (LM)	280 lm
INTENSITY RATING (CD)	130
POWER CONSUMPTION (W)	3W
LUMINAIRE EFFICACY (LM/W)	93 lm/W
DRIVE CURRENT (mA)	350mA
FORWARD VOLTAGE (V DC)	8.5V DC



INGRESS RATING	IP54
IMPACT RATING	IK02
COMPLIANCE	IEC/EN 60598-1:2015
	IEC/EN 60598-2-2:2012

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	>95 Ra
IES TM-30 COLOUR FIDELITY (Rf)	>95
IES TM-30 COLOUR GAMUT (Rg)	>95
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 +35 °C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	DALI dimmable
	1-10V dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	2 Core PVC (80 °C)
CABLE SIZE	2 off 22 AWG 7/30 (0.33mm2) Copper Strands
CABLE LENGTH	2000mm
CONNECTOR TYPE	N/A
WEIGHT	35g
FIRE RATED	N/A



WWW.JOHNCULLENLIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81



