

SQUARE TRIMLESS PURE 50 BLACK
SUPERWIDE 2700K
KSSL02TP27SW

LUMINAIRE REF:

PROJECT REF:





BLACK RAL 9005

ARCHITECTURAL DIRECTIONAL SUPERWIDE BEAM BLACK TRIMLESS DOWNLIGHT

Our Square Pure 50 LED downlight uses an extra slim-line bezel with a deep 25mm dual black baffle system to help reduce glare. The downlight is suitable for plasterboard ceilings and can tilt up to 35 degrees and rotate a full 360 degrees.

Note: This luminaire cannot be used in conjunction with the John Cullen Lighting Fire Plate Accessory. For applications requiring fire rating a fire box should be built into the ceiling void or a John Cullen Lighting specified fire hood should be used.



SUPERWIDE

ACCESSORIES



INTUMESCENT
FIREHOOD SMALL
ACFHXXSM1



HONEYCOMB
INSERT 50MM
ACHC50MM1



SPREADER LENS
50MM
ACLL50MM1



SANDBLASTED
GLASS LENS 50MM
ACSG50MM1



SOFTENING LENS
50MM
ACSL50MM2



WWW.JOHN CULLEN LIGHTING.COM


UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

SQUARE TRIMLESS PURE 50 BLACK
SUPERWIDE 2700K
KSSL02TP27SW

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	SUPERWIDE
BEAM ANGLE (°)	45°
LED SOURCE LUMENS (LM)	1344 lm
LUMINAIRE LUMENS (LM)	597 lm
INTENSITY RATING (CD)	1157
POWER CONSUMPTION (W)	12W
LUMINAIRE EFFICACY (LM/W)	50 lm/W
DRIVE CURRENT (mA)	350 mA
FORWARD VOLTAGE (V DC)	36V DC



INGRESS RATING	IP20
IMPACT RATING	N/A
COMPLIANCE	

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	98 Ra
IES TM-30 COLOUR FIDELITY (Rf)	95
IES TM-30 COLOUR GAMUT (Rg)	99.4
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 ... +35 °C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	DALI/Phase cut/1-10V

OTHER DATA	
Cable Type	2 Core Silicone (180 °C)
Cable Size	6.4mm OD - 2 off 24/0.2 (0.75mm2)
Cable Length	350mm
Connector Type	OJ-602B
Weight	N/A
Fire rated	Yes

