

ARINE PURE 30 MINI-TRIM ADJUSTABLE WHITE  
WIDE  
KAR3MTA0011WI

LUMINAIRE REF:



PROJECT REF:



WHITE RAL 9003 TEXTURED

MINI-TRIM ADJUSTABLE WHITE WIDE 2700K

The Arine 30 Mini-Trim is a dedicated adjustable superyacht downlight. It has a precision engineered fixing mechanism - a rear fixing plate and frame, which allow positioning in different ceiling thicknesses of deckhead. The diameter of the fixing plate allows a leading full 30 degree tilt by preventing incursion from other ceiling elements. It comes with our dedicated LED 30 engine with high CRI and superior quality light output.



WIDE

ACCESSORIES



HONEYCOMB  
INSERT 23MM  
ACHC23MM1



SPREADER LENS  
23MM  
ACLL23MM1



SANDBLASTED  
GLASS LENS 23MM  
ACSG23MM1



SOFTENING LENS  
23MM  
ACSL23MM1




ARINE PURE 30 MINI-TRIM ADJUSTABLE WHITE  
WIDE

KAR3MTA0011WI

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	WIDE
BEAM ANGLE (°)	52°
LED SOURCE LUMENS (LM)	381
LUMINAIRE LUMENS (LM)	330
INTENSITY RATING (CD)	550
POWER CONSUMPTION (W)	4
LUMINAIRE EFFICACY (LM/W)	83
DRIVE CURRENT (mA)	350mA
FORWARD VOLTAGE (V DC)	11V DC



INGRESS RATING	IP54
IMPACT RATING	IK03
COMPLIANCE	IEC/EN 60598-1
	IEC/EN 60598-2-2

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	>90 Ra
IES TM-30 COLOUR FIDELITY (Rf)	>90
IES TM-30 COLOUR GAMUT (Rg)	>90
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 ... +25 °C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	1-10V dimmable
	DALI dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	2 Core Silicone (105°C)
CABLE SIZE	4.1mm OD - 2 off 17/0.15
CABLE LENGTH	300mm
CONNECTOR TYPE	OJ-602B
WEIGHT	N/A
FIRE RATED	N/A

