

POLESPRING PURE 40 WHITE MEDIUM 2023  
KPS40XPU27ME01

LUMINAIRE REF:

PROJECT REF:





WHITE RAL 9003 TEXTURED

DIRECTIONAL TRIM MINIATURE DOWNLIGHT WITH MINIMAL BEZEL

Our flagship Polespring 40 has been upgraded with an increased aperture delivering market-leading performance in this smaller fitting. New "clip-fit" mechanics create a modular design for a more sustainable product. The standard white finish is now a textured matt RAL9003. The fitting still comes with the 30° tilt and extra deep 25mm black baffle to minimise glare.

It comes as standard with the Pure 40 engine and a tool less plug for connecting the LED driver. NB: The cut-out of this product has increased to 54MM.



MEDIUM

ACCESSORIES



HONEYCOMB  
INSERT 42MM  
ACHC42MM1



SPREADER LENS  
42MM  
ACLL42MM1



SANDBLASTED  
GLASS LENS 42MM  
ACSG42MM1



SOFTENING LENS  
42MM  
ACSL42MM1



WWW.JOHN CULLEN LIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81




# POLESPRING PURE 40 WHITE MEDIUM 2023

## KPS40XPU27ME01

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	MEDIUM
BEAM ANGLE (°)	21°
LED SOURCE LUMENS (LM)	680
LUMINAIRE LUMENS (LM)	361 lm
INTENSITY RATING (CD)	2063
POWER CONSUMPTION (W)	9
LUMINAIRE EFFICACY (LM/W)	40 lm/W
DRIVE CURRENT (mA)	500mA
FORWARD VOLTAGE (V DC)	17V DC






TM66	2.3 (LIA Assured Verification Score)
INGRESS RATING	IP54 (Front Face)
IMPACT RATING	IK03
COMPLIANCE	IEC/EN 60598-1
	IEC/EN 60598-2-2

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	98 Ra
IES TM-30 COLOUR FIDELITY (Rf)	>95
IES TM-30 COLOUR GAMUT (Rg)	100
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 ... +25 °C


ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	DALI dimmable
	1-10V dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
Cable Type	2 Core Silicone (180 °C)
Cable Size	6.4mm OD - 2 off 24/0.2 (0.75mm2)
Cable Length	300mm
Connector Type	OJ-602B
Weight	N/A
Fire rated	Yes

COLOUR VECTOR GRAPHIC



Colour Rendering Index



WWW.JOHN CULLEN LIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East &amp; APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

