

LUCCA 60 TRIMLESS MEDIUM STAINLESS  
STEEL WITH COWL

ULL6FWG172

LUMINAIRE REF:

PROJECT REF:





STAINLESS STEEL

STAINLESS STEEL MEDIUM BEAM TRIMLESS UPLIGHT FOR USE IN ARCHITECTURAL LIGHTING, BOTH INSIDE AND OUT.

The Lucca 60 is an energy efficient trimless LED midi uplight. It is ideal for creating stunning uplighting effects to columns, arches, window reveals, walls and trees. Available in narrow, medium and wide distributions, with additional elliptical and asymmetric variants for wall grazing and wall washing. Trimless fittings come with a burial tube as standard.

It is IP67 rated so ideal for use both inside and out. If using inside, the warranty increases to 5 years.



MEDIUM

ACCESSORIES



IP66 ENCLOSURE  
FOR DRIVER  
LARGE  
ACENIPLRG



IP66 ENCLOSURE  
FOR DRIVER  
SMALL  
ACENIPSMML




LUCCA 60 TRIMLESS MEDIUM STAINLESS  
STEEL WITH COWL

ULL6FWG172

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	MEDIUM
BEAM ANGLE (°)	27°
LED SOURCE LUMENS (LM)	516 lm
LUMINAIRE LUMENS (LM)	230 lm
INTENSITY RATING (CD)	858
POWER CONSUMPTION (W)	6W
LUMINAIRE EFFICACY (LM/W)	38.3 lm/W
DRIVE CURRENT (mA)	500mA
FORWARD VOLTAGE (V DC)	12V DC



INGRESS RATING	IP67
IMPACT RATING	N/A
COMPLIANCE	IEC/EN 60598-1:2015
	IEC/EN 60598-2-2:2012
	IEC/EN 60598-2-13:2006

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	>90 Ra
IES TM-30 COLOUR FIDELITY (Rf)	>90
IES TM-30 COLOUR GAMUT (Rg)	>95
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 ... +40 °C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	DALI dimmable
	1-10V dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	2 Core Silicone (180 °C)
CABLE SIZE	2 off 7/0.2 (0.22mm2)
CABLE LENGTH	1000mm
CONNECTOR TYPE	N/A
WEIGHT	N/A
FIRE RATED	N/A

