

POLEFINITY IP54 PURE 40 WHITE WIDE 2700K  
2023  
KPF401PU27W12

LUMINAIRE REF:

PROJECT REF:





WHITE RAL 9003 TEXTURED

DIRECTIONAL TRUE TRIMLESS MINIATURE DOWNLIGHT

We have upgraded our Polefinity 40 miniature true trimless low glare directional architectural downlight for 2023. We have retained the 360° rotation and 30° tilt mechanism, alongside a 25mm extra deep black baffle allows for a low glare, minimal lighting solution. We have introduced "clip-fit" mechanics as part of a modular design, creating a sustainable product architecture for the circular economy. The luminaire is now IP54 as standard, with the option of an IP65 accessory. The standard white finish is now a textured matt RAL9003. It comes with a contractor optimised frame for installing at first fix. No special tools required.

It now comes as standard with the new Pure 40 engine. The engine features a patented twist and lock LED engine mount for interchangeable components on site with no hand tools required and a tool less plug for connecting the LED driver. NB: The cut-out of this product has increased to 71MM.



WIDE

ACCESSORIES



HONEYCOMB  
INSERT 42MM  
ACHC42MM1



SPREADER LENS  
42MM  
ACLL42MM1




SOFTENING LENS  
42MM  
ACSL42MM1



## PROJECT REF:

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	>95 Ra
IES TM-30 COLOUR FIDELITY (Rf)	>95
IES TM-30 COLOUR GAMUT (Rg)	>98
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 ... +25 °C

OTHER DATA	
CABLE TYPE	2 Core Silicone (180 °C)
CABLE SIZE	6.4mm OD - 2 off 24/0.2 (0.75mm2)
CABLE LENGTH	300mm
CONNECTOR TYPE	OJ-602B
WEIGHT	N/A
FIRE RATED	Yes



UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81