

SQUARE TRIM PURE 50 IP BLACK NARROW

2700K

KSST02TP27NA54

LUMINAIRE REF:



PROJECT REF:



BLACK RAL 9005

ARCHITECTURAL DIRECTIONAL IP NARROW BEAM BLACK DOWNLIGHT

Our Square Pure 50 IP LED downlight uses an extra slim-line bezel with a deep 25mm dual black baffle system to help reduce glare. The downlight is suitable for wet areas and for plasterboard ceilings and can tilt up to 35 degrees and rotate a full 360 degrees.



NARROW

ACCESSORIES

- 

INTUMESCENT
FIREHOOD SMALL
ACFHXXSM1
- 

HONEYCOMB
INSERT 50MM
ACHC50MM1
- 

SPREADER LENS
50MM
ACLL50MM1
- 

SANDBLASTED
GLASS LENS 50MM
ACSG50MM1
- 

SOFTENING LENS
50MM
ACSL50MM2



SQUARE TRIM PURE 50 IP BLACK NARROW


2700K

KSST02TP27NA54

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	NARROW
BEAM ANGLE (°)	22°
LED SOURCE LUMENS (LM)	1344 lm
LUMINAIRE LUMENS (LM)	731 lm
INTENSITY RATING (CD)	4014
POWER CONSUMPTION (W)	12W
LUMINAIRE EFFICACY (LM/W)	61 lm/W
DRIVE CURRENT (mA)	350 mA
FORWARD VOLTAGE (V DC)	36V DC



INGRESS RATING	IP54 (Front)/IP20 (Rear)
IMPACT RATING	N/A
COMPLIANCE	

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	98 Ra
IES TM-30 COLOUR FIDELITY (Rf)	95
IES TM-30 COLOUR GAMUT (Rg)	99.4
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 ... +35 °C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	DALI/Phase cut/1-10V

OTHER DATA	
CABLE TYPE	2 Core Silicone (180 °C)
CABLE SIZE	6.4mm OD - 2 off 24/0.2 (0.75mm2)
CABLE LENGTH	350mm
CONNECTOR TYPE	OJ-602B
WEIGHT	N/A
FIRE RATED	Yes

