

ARINE PURE 30 MINI-TRIM ADJUSTABLE WHITE
NARROW
KAR3MTA9003NA

LUMINAIRE REF:



PROJECT REF:



WHITE RAL 9003 TEXTURED

MINI-TRIM ADJUSTABLE WHITE NARROW 2700K

The Arine 30 Mini-Trim is a dedicated adjustable superyacht downlight. It has a precision engineered fixing mechanism - a rear fixing plate and frame, which allow positioning in different ceiling thicknesses of deckhead. The diameter of the fixing plate allows a leading full 30 degree tilt by preventing incursion from other ceiling elements. It comes with our dedicated LED 30 engine with high CRI and superior quality light output.



NARROW

ACCESSORIES



HONEYCOMB
INSERT 23MM
ACHC23MM1



SPREADER LENS
23MM
ACLL23MM1



SANDBLASTED
GLASS LENS 23MM
ACSG23MM1



SOFTENING LENS
23MM
ACSL23MM1




ARINE PURE 30 MINI-TRIM ADJUSTABLE WHITE
NARROW

KAR3MTA9003NA

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	NARROW
BEAM ANGLE (°)	11.5°
LED SOURCE LUMENS (LM)	150
LUMINAIRE LUMENS (LM)	148
INTENSITY RATING (CD)	2446
POWER CONSUMPTION (W)	2
LUMINAIRE EFFICACY (LM/W)	74
DRIVE CURRENT (mA)	700mA
FORWARD VOLTAGE (V DC)	3V DC



INGRESS RATING	IP54
IMPACT RATING	IK03
COMPLIANCE	IEC/EN 60598-1
	IEC/EN 60598-2-2

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	>95 Ra
IES TM-30 COLOUR FIDELITY (Rf)	>90
IES TM-30 COLOUR GAMUT (Rg)	>95
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 ... +25 °C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	1-10V dimmable
	DALI dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	2 Core Silicone (105°C)
CABLE SIZE	4.1mm OD - 2 off 17/0.15
CABLE LENGTH	300mm
CONNECTOR TYPE	OJ-602B
WEIGHT	N/A
FIRE RATED	N/A

