



ETTA WHITE 1ST GENERATION SCFU27012


LUMINAIRE REF:

PROJECT REF:



The Etta is a precision engineered low glare LED under cupboard light that can also be used for recessed task and display lighting. It is suitable for under shelf lighting, bespoke cabinetry, kitchens and marine lighting

WHITE



ACCESSORIES



SURFACE MOUNT COLLAR ALUMINIUM ACUCSM102

WWW.JOHNCULLENLIGHTING.COM UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

 \odot John Cullen Lighting 2024. Technical data figures are for guidance only and are subject to $\pm 5\%$ tolerance We reserve the right to change the design and specification of our product range without prior notice. E&OE





ETTA WHITE 1ST GENERATION LUMINAIRE REF: SCFU27012 PROJECT REF: SPECIFICATION WIDE BEAM ANGLE (°) 100° LED SOURCE LUMENS (LM) N/A LUMINAIRE LUMENS (LM) N/A INTENSITY RATING (CD) N/A POWER CONSUMPTION (W) N/A LUMINAIRE EFFICACY (LM/W) N/A DRIVE CURRENT (mA) N/A FORWARD VOLTAGE (V DC) N/A INGRESS RATING IP54 COLOUR TEMPERATURE 2700K IMPACT RATING N/A CIE CRI AVAILABLE AS N/A IES TM-30 COLOUR FIDELITY (Rf) N/A COMPLIANCE IEC/EN 60598-1:2015 IEC/EN 60598-2-2:2012 IES TM-30 COLOUR GAMUT (Rg) N/A BINNING N/A LIFETIME L70/B10 (HOURS) N/A AMBIENT TEMPERATURE (Ta) N/A ELECTRICAL OTHER DATA

SOURCE TYPE	LED	CABLE TYPE	N/A
PRODUCT CLASS	Class III (SELV low voltage)	CABLE SIZE	2 off 7/0.2 (0.22mm2) Tinned Copper Strands
DIMMING PROTOCOL	1-10V dimmable	CABLE LENGTH	200mm
	DALI dimmable	CONNECTOR TYPE	N/A
	Mains dimmable (phase cut dimming)	WEIGHT	70g
	Switched	FIRE RATED	N/A

WWW.JOHNCULLENLIGHTING.COM UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

© John Cullen Lighting 2024. Technical data figures are for guidance only and are subject to ±5% tolerance We reserve the right to change the design and specification of our product range without prior notice. E&OE

