

CONTOUR HDX 2400K LED STRIP 1ST
GENERATION
LI0924681

LUMINAIRE REF:


PROJECT REF:



N/A

The Contour products are used to provide detail lighting. Often to highlight features of joinery, stair treads or illuminate shelving where you require something to be illuminated instead of providing a light source.

Contour strips can be cut every 50mm and are sold by the metre.





CONTOUR HDX 2400K LED STRIP 1ST
GENERATION

LI0924681

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	LAMBERTIAN
BEAM ANGLE (°)	120°
LED SOURCE LUMENS (LM)	N/A
LUMINAIRE LUMENS (LM)	N/A
INTENSITY RATING (CD)	N/A
POWER CONSUMPTION (W)	N/A
LUMINAIRE EFFICACY (LM/W)	N/A
DRIVE CURRENT (mA)	N/A
FORWARD VOLTAGE (V DC)	N/A

INGRESS RATING	IP68
IMPACT RATING	N/A
COMPLIANCE	

COLOUR TEMPERATURE	2400K
CIE CRI AVAILABLE AS	>90 Ra
IES TM-30 COLOUR FIDELITY (Rf)	90
IES TM-30 COLOUR GAMUT (Rg)	>96
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	N/A

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	1-10V dimmable
	DALI dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	N/A
CABLE SIZE	N/A
CABLE LENGTH	200mm
CONNECTOR TYPE	Soldered by electrician on site
WEIGHT	N/A
FIRE RATED	N/A

