PAGE 1 OF 2



## **CONTOUR HD 2400K LED STRIP FOR SAUNAS**


LICN126MP241MIP67

LUMINAIRE REF:

PROJECT REF:



This specialist Contour HD strip is designed specifically for use in Saunas where withstanding both high temperatures and moisture are important.





WWW.JOHNCULLENLIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

PAGE 2 OF 2 08/05/2024 V1.73



## **CONTOUR HD 2400K LED STRIP FOR SAUNAS**

LUMINAIRE REF:

LICN126MP241MIP67

PROJECT REF:

SPECIFICATION	LAMBERTIAN
BEAM ANGLE (°)	120°
LED SOURCE LUMENS (LM)	980lm
LUMINAIRE LUMENS (LM)	980lm/M
INTENSITY RATING (CD)	N/A
POWER CONSUMPTION (W)	9.6W
LUMINAIRE EFFICACY (LM/W)	102.08lm/w
DRIVE CURRENT (mA)	400
FORWARD VOLTAGE (V DC)	24V

INGRESS RATING	IP67
IMPACT RATING	N/A
COMPLIANCE	CE
	UL

COLOUR TEMPERATURE	2400K
CIE CRI AVAILABLE AS	>90
IES TM-30 COLOUR FIDELITY (Rf)	N/A
IES TM-30 COLOUR GAMUT (Rg)	N/A
BINNING	2 step
LIFETIME L70/B10 (HOURS)	60000
AMBIENT TEMPERATURE (Ta)	'-20~45°C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	DALI dimmable
	1-10V dimmable
	Switched

OTHER DATA	
CABLE TYPE	UL3239
CABLE SIZE	18AWG
CABLE LENGTH	0.3mtr
CONNECTOR TYPE	N/A
WEIGHT	0.45kg
FIRE RATED	N/A



WWW.JOHNCULLENLIGHTING.COM

 $\mathsf{UK} + 44~(0)~20~7371~9000~|~\mathsf{Middle~East~\&~APAC~+971~(0)}~4~321~114~|~\mathsf{Europe~+33~(0)9}~61~68~22~81$ 

