

CONTOUR HD HIGH LUMEN 2700K 16W LED
STRIP IP20
LICN160HP271MIP20


LUMINAIRE REF:

PROJECT REF:



N/A

This specialist Contour HD strip is ideal for when you are looking for a higher lumen output where more punch is required. It can highlight features such as joinery, stair treads, coving or under cabinets to create floating effects for larger scale projects where you require a line of light rather than a point source.




ACCESSORIES




CONTOUR
CURVED CORNER
ALUMINIUM
PROFILE 2024 1M
LICNAP10021M



CONTOUR
CURVED CORNER
ALUMINIUM
PROFILE 2024 2M
LICNAP10022M



CONTOUR
STANDARD
ALUMINIUM
PROFILE 2024 1M
LICNAP12021M



CONTOUR
STANDARD
ALUMINIUM
PROFILE 2024 2M
LICNAP12022M





CONTOUR HD HIGH LUMEN 2700K 16W LED
STRIP IP20
LICN160HP271MIP20

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	LAMBERTIAN
BEAM ANGLE (°)	120°
LED SOURCE LUMENS (LM)	1790lm
LUMINAIRE LUMENS (LM)	1790lm/M
INTENSITY RATING (CD)	N/A
POWER CONSUMPTION (W)	16W
LUMINAIRE EFFICACY (LM/W)	111.87lm/w
DRIVE CURRENT (mA)	666
FORWARD VOLTAGE (V DC)	24V

INGRESS RATING	IP20
IMPACT RATING	N/A
COMPLIANCE	CE
	UL

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	>95
IES TM-30 COLOUR FIDELITY (Rf)	N/A
IES TM-30 COLOUR GAMUT (Rg)	N/A
BINNING	2 step
LIFETIME L70/B10 (HOURS)	60000
AMBIENT TEMPERATURE (Ta)	-20~45°C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	DALI dimmable
	1-10V dimmable
	Switched

OTHER DATA	
CABLE TYPE	UL1007
CABLE SIZE	22AWG
CABLE LENGTH	0.3mtr
CONNECTOR TYPE	N/A
WEIGHT	0.15KG
FIRE RATED	N/A

