

## CONTOUR HD RGBW LED STRIP IP20 LICNRGBWHP1MIP20


LUMINAIRE REF:

PROJECT REF:



N/A

This specialist Contour LED strip delivers both RGB colour changing along with a white too. It is ideal for locations where you require a colour changing effect along with a white for different occasions.



### ACCESSORIES



CONTOUR CURVED CORNER ALUMINIUM PROFILE 2024 1M  
LICNAP10021M



CONTOUR CURVED CORNER ALUMINIUM PROFILE 2024 2M  
LICNAP10022M



CONTOUR STANDARD ALUMINIUM PROFILE 2024 1M  
LICNAP12021M



CONTOUR STANDARD ALUMINIUM PROFILE 2024 2M  
LICNAP12022M



CONTOUR MICRO PROFILE 2024 1M  
LICNAPCD10101M



CONTOUR MICRO PROFILE 2024 2M  
LICNAPCD10102M



**CONTOUR HD RGBW LED STRIP IP20**  
**LICNRGBWHP1MIP20**

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	LAMBERTIAN
BEAM ANGLE (°)	120°
LED SOURCE LUMENS (LM)	1180lm
LUMINAIRE LUMENS (LM)	1180lm/M
INTENSITY RATING (CD)	N/A
POWER CONSUMPTION (W)	12W
LUMINAIRE EFFICACY (LM/W)	59lm/W
DRIVE CURRENT (mA)	833
FORWARD VOLTAGE (V DC)	24V

INGRESS RATING	IP20
IMPACT RATING	N/A
COMPLIANCE	CE
	UL

COLOUR TEMPERATURE	RGBW-2700K
CIE CRI AVAILABLE AS	>90
IES TM-30 COLOUR FIDELITY (Rf)	N/A
IES TM-30 COLOUR GAMUT (Rg)	N/A
BINNING	2 step
LIFETIME L70/B10 (HOURS)	60000
AMBIENT TEMPERATURE (Ta)	-20~45°C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	DALI dimmable
	1-10V dimmable
	Switched

OTHER DATA	
CABLE TYPE	UL1007
CABLE SIZE	22AWG
CABLE LENGTH	0.3mtr
CONNECTOR TYPE	N/A
WEIGHT	0.15KG
FIRE RATED	N/A

WWW.JOHN CULLEN LIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East &amp; APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81