

VORSA TRACK 50 SUPER WIDE BLACK 0-10V
2024
SLVT5SWO25AN2



LUMINAIRE REF:

PROJECT REF:



BLACK RAL 9005

The updated Vorsa Track 50 is a versatile "click and fit" track mounted directional spotlight. It has been re-engineered for 2024 with a cleaner aesthetic, an increased light output and an industry-leading light output at 98 CRI. Interchangeable optics allow for a range of beam distributions, all easy to fit on-site. Its track architecture facilitates easy changing between different size Vorsa heads when commissioning a scheme. We have introduced a new innovative screwless self-supporting tilt mechanism. This fitting is ideal for use in areas of key areas of the home and is perfect for use on beams and concrete ceilings where recessed fittings are unsuitable. The Vorsa Track 50 can be used on a range of Stucchi track systems including recessed, surface mounted and suspended. Please ask for full details. The range has been built to the principles of the circular economy to not only maximise resources but also to reduce waste and environmental impact.



SUPER WIDE

ACCESSORIES

							
VORSA 50 HONEYCOMB INSERT Ø48MM X 3MM ACHCVO502	VORSA 50 SAND BLASTED GLASS INSERT Ø48MM X 3MM ACSGVO502	VORSA 50 HIGH TRANSMISSION SOFTENING GLASS INSERT Ø48MM X 3MM ACSLVO502	VORSA STANDARD EVO TRACK WHITE - 1M/2M SLVTF1012/2012	VORSA STANDARD EVO TRACK BLACK - 1M/2M SLVTF1022/2022	VORSA RECESSED EVO TRACK BLACK - 1M/2M SLVTR1022/2022	VORSA SUSPENDED TRACK WHITE - 1M/2M SLVTW1012/2012	VORSA SUSPENDED TRACK BLACK - 1M/2M SLVTW1022/2022




VORSA TRACK 50 SUPER WIDE BLACK 0-10V
2024
SLVT5SW025AN2

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	SUPER WIDE
BEAM ANGLE (°)	50°
LED SOURCE LUMENS (LM)	1290
LUMINAIRE LUMENS (LM)	780
INTENSITY RATING (CD)	1310
POWER CONSUMPTION (W)	12
LUMINAIRE EFFICACY (LM/W)	65
DRIVE CURRENT (mA)	N/A
FORWARD VOLTAGE (V DC)	N/A



TM66	2.3 (LIA Assured Verification Score)
INGRESS RATING	IP20
IMPACT RATING	IK03
COMPLIANCE	IEC 60598-1:2020
	IEC 60598-2-1:2020

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	>95 Ra
IES TM-30 COLOUR FIDELITY (Rf)	>95
IES TM-30 COLOUR GAMUT (Rg)	≈100
BINNING	2-step
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 ... +25 °C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	DALI dimmable

OTHER DATA	
CABLE TYPE	FEP (200 °C)
CABLE SIZE	N/A
CABLE LENGTH	N/A
CONNECTOR TYPE	Track Adapter
WEIGHT	375
FIRE RATED	N/A

