

LUCCA 30 WIDE STAINLESS STEEL 2024  
ULL3TW172



LUMINAIRE REF:

PROJECT REF:



STAINLESS STEEL

The new Lucca 30 is an energy efficient LED miniature uplight incorporating new ProVent technology which minimises condensation and improves robustness. Built for the circular economy, the LED engine is now fully serviceable. It is ideal for creating stunning uplighting effects to columns, arches, window reveals and along walls. It comes with narrow, medium or wide beams to suit your projects. It is IP67 rated so ideal for use both inside and out. Fittings come with 1m of cable as standard. Custom cable lengths are available upon request. If using inside, the warranty increases to 5 years.



WIDE

ACCESSORIES



IP66 ENCLOSURE  
FOR DRIVER  
LARGE  
ACENIPLRG



IP66 ENCLOSURE  
FOR DRIVER  
SMALL  
ACENIPSML



LUCCA 30 TRIM  
BURIAL SLEEVE  
ACL3TRS2



WWW.JOHN CULLEN LIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81




LUCCA 30 WIDE STAINLESS STEEL 2024

ULL3TW172

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	350mA	500mA	700mA
BEAM ANGLE (°)	36°	36°	36°
LED SOURCE LUMENS (LM)	101	137	181
LUMINAIRE LUMENS (LM)	62	84	111
LUMINAIRE EFFICACY (LM/W)	62	56	53
INTENSITY RATING (CD)	154	212	282
POWER CONSUMPTION (W)	1	1.5	2.1
DRIVE CURRENT (mA)	350	500	700
FORWARD VOLTAGE (V DC)	3	3	3
MAX TEMPERATURE (°C)	40	40	35



TM66	2.4 (LIA Assured Verification Score)
INGRESS RATING	IP65 + IP67
IMPACT RATING	IK08
COMPLIANCE	BS EN 60598-2-13: 2006+A1: 2012+A2: 2016 BS EN IEC 60598-1:2021 BS EN 62493:2015+A1:2022 BS EN IEC 62031:2020+A11:2021

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	98 Ra
IES TM-30 COLOUR FIDELITY (Rf)	93.8
IES TM-30 COLOUR GAMUT (Rg)	98.1
BINNING	2 SDCM (Equivalent)
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	N/A

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	1-10V dimmable DALI dimmable Mains dimmable (phase cut dimming) Switched

OTHER DATA	
Cable Type	2 Core Silicone (180°C)
Cable Size	6mm OD - 2 off 24/0.2 (0.75mm2)
Cable Length	1000mm
Connector Type	N/A
Weight	N/A
Fire rated	N/A



WWW.JOHN CULLEN LIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81