

### LUCCA 30 STEPLIGHT NARROW STAINLESS STEEL WITH COWL 2024 SLL3TNG172

### LUMINAIRE REF:


PROJECT REF:




The new Lucca 30 is an energy efficient LED miniature steplight with a glare cowl incorporating new ProVent technology which minimises condensation and improves robustness. Built for the circular economy, the LED engine is now fully serviceable. It is ideal for creating stunning skimming light across steps. It comes with narrow, medium or wide beams to suit your projects. This product can also be used as a downlight.

It is IP67 rated so ideal for use both inside and out. Fittings come with 1m of cable as standard. Custom cable lengths are available upon request. If using inside, the warranty increases to 5 years.

#### STAINLESS STEEL





NARROW

### ACCESSORIES





FOR DRIVER LARGE ACENIPLRG P66 ENCLOSUF FOR DRIVER SMALL ACENIPSML



WWW.JOHNCULLENLIGHTING.COM UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

# IOHN CI II I EN

700mA

11°

137

92 40

1401

700

3

## LUCCA 30 STEPLIGHT NARROW STAINLESS STEEL WITH COWL 2024 SLL3TNG172

350mA

11°

78

55

50

829


1.1

350

3

### LUMINAIRE REF:

PROJECT REF:



COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	92 Ra
IES TM-30 COLOUR FIDELITY (Rf)	92.1
IES TM-30 COLOUR GAMUT (Rg)	99.4
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	N/A

OTHER DATA CABLE TYPE

CABLE SIZE

WEIGHT FIRE RATED N/A

CABLE LENGTH

ONNECTOR TYPE

2 Core Silicone (180°C)

1000mr

N/A N/A

6mm OD - 2 off 24/0.2 (0.75mm2

MAX TEMPERATURE (°C)	40	40	35	
TM	66 2.4 (L	IA Assured Verification Sc	ore)	
INGRESS RATIN	IG IP65 ·	+ IP67		
IMPACT RATIN	IG IK08			
COMPLIAN	CE BS EN	↓ 60598-2-13: 2006+A1:	2012+A2: 2016	
	BS EN	IEC 60598-1:2021		
	BS EN	62493:2015+A1:2022		
	BS EN	IEC 62031:2020+A11:20	021	
ELECTRIC	4L			
SOURCE TY	PE LED			
DDODUCT CLA				

500mA

11°

105

73

45

1104

1.6

500

SOURCE TYPI
PRODUCT CLAS
DIMMING PROTOCO

SPECIFICATION

BEAM ANGLE (°)

LED SOURCE LUMENS (LM)

LUMINAIRE LUMENS (LM)

INTENSITY RATING (CD)

DRIVE CURRENT (mA)


LUMINAIRE EFFICACY (LM/W)

POWER CONSUMPTION (W)

FORWARD VOLTAGE (V DC)

LED
Class III (SELV low voltage)
1-10V dimmable
DALI dimmable
Mains dimmable (phase cut dimming)
Switched







### WWW.JOHNCULLENLIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

3

WARRANTY