

LUCCA 30 STEPLIGHT MEDIUM BRASS WITH COWL 2024 SLL3TMG042

LUMINAIRE REF:


PROJECT REF:



The new Lucca 30 is an energy efficient LED miniature steplight with a glare cowl incorporating new ProVent technology which minimises condensation and improves robustness. Built for the circular economy, the LED engine is now fully serviceable. It is ideal for creating stunning skimming light across steps. It comes with narrow, medium or wide beams to suit your projects. This product can also be used as a downlight.

It is IP67 rated so ideal for use both inside and out. Fittings come with 1m of cable as standard. Custom cable lengths are available upon request. If using inside, the warranty increases to 5 years.

BRASS





MEDIUM

ACCESSORIES





FOR DRIVER LARGE ACENIPLRG IP66 ENCLOSURE FOR DRIVER SMALL ACENIPSML



WWW.JOHNCULLENLIGHTING.COM UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

OHN ^i∥ieN

700mA

20°

181

103

49

691

2.1

700

3

LUCCA 30 STEPLIGHT MEDIUM BRASS WITH COWL 2024 SLL3TMG042

500mA

20°

137

78

52

520

1.5

500

TM66 2.4 (LIA Assured Verification Score)

350mA

20°

101

57


57

380

350

LUMINAIRE REF:

PROJECT REF:



COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	98 Ra
5 TM-30 COLOUR FIDELITY (Rf)	94
S TM-30 COLOUR GAMUT (Rg)	98.4
BINNING	2 SDCM (Equivalent)
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	N/A
OTHER DATA	

IES TM-

IES TM

OTHER DATA	
CABLE TYPE	2 Core Silicone (180°C)
CABLE SIZE	6mm OD - 2 off 24/0.2 (0.75mm2)
CABLE LENGTH	1000mm
CONNECTOR TYPE	N/A
WEIGHT	N/A
FIRE RATED	N/A

INGRESS RATING	IP65 + IP67	
IMPACT RATING	IK08	
COMPLIANCE	BS EN 60598-2-13: 2006+A1: 2012+A2: 2016	
	BS EN IEC 60598-1:2021	
	BS EN 62493:2015+A1:2022	
	BS EN IEC 62031:2020+A11:2021	
ELECTRICAL		
SOURCE TYPE	LED	
PRODUCT CLASS	Class III (SELV low voltage)	
IMING PROTOCOL	1-10V dimmable	
	DALI dimmable	

ELECT

SOURCE PRODUCT DIMMING PROT

SPECIFICATION

BEAM ANGLE (°)

LED SOURCE LUMENS (LM)

LUMINAIRE LUMENS (LM)

INTENSITY RATING (CD)


DRIVE CURRENT (mA)


LUMINAIRE EFFICACY (LM/W)

POWER CONSUMPTION (W)

FORWARD VOLTAGE (V DC)


MAX TEMPERATURE (°C)






Mains dimmable (phase cut dimming)

Switched









3 WARRANTY

WWW.JOHNCULLENLIGHTING.COM UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81