

LUCCA 30 STEPLIGHT WIDE BRONZE 2024 SLL3TW062

LUMINAIRE REF:

PROJECT REF:



BRONZE ANODISED

The new Lucca 30 is an energy efficient LED miniature steplight incorporating new ProVent technology which minimises condensation and improves robustness. Built for the circular economy, the LED engine is now fully serviceable. It is ideal for creating stunning skimming light across steps. It comes with narrow, medium or wide beams to suit your projects. This product can also be used as a downlight.

It is IP67 rated so ideal for use both inside and out. Fittings come with 1m of cable as standard. Custom cable lengths are available upon request. If using inside, the warranty increases to 5 years.

41 ut Out ø2





WIDE

ACCESSORIES



IP66 ENCLOSURE LARGE



FOR DRIVER ACENIPLRG

IP66 ENCLOSURE FOR DRIVER SMALL ACENIPSML



UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

© John Cullen Lighting 2024. Technical data figures are for guidance only and are subject to ±5% tolerance We reserve the right to change the design and specification of our product range without prior notice. E&OE



BRITISH UK CA

WWW.JOHNCULLENLIGHTING.COM



JOHN A III EN

700mA

36°

181

111

53

282

2.1

700

3

LUCCA 30 STEPLIGHT WIDE BRONZE 2024 SLL3TW062

350mA

36°

101

62

62

154

350

40

TM66

INGRESS RATING IMPACT RATING

COMPLIANCE

SPECIFICATION BEAM ANGLE (°)

LED SOURCE LUMENS (LM)

LUMINAIRE LUMENS (LM)

INTENSITY RATING (CD)

DRIVE CURRENT (mA)

LUMINAIRE EFFICACY (LM/W)

POWER CONSUMPTION (W)

FORWARD VOLTAGE (V DC)

MAX TEMPERATURE (°C)

500mA

36°

137

84

56

212

1.5

500

40


LUMINAIRE REF:

PROJECT REF:

IES TM-30 COLO

IES TM-30 COLC

AMBIENT TEN



COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	98 Ra
TM-30 COLOUR FIDELITY (Rf)	93.8
TM-30 COLOUR GAMUT (Rg)	98.1
BINNING	2 SDCM (Equivalent)
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	N/A
OTHER DATA	
CABLE TYPE	2 Core Silicone (180°C)
CABLE SIZE	6mm OD - 2 off 24/0.2 (0.75mm2)
CABLE LENGTH	1000mm
CONNECTOR TYPE	N/A
WEIGHT	N/A

2.4 (LIA Assured Verification Score)
IP65 + IP67
IK08
BS EN 60598-2-13: 2006+A1: 2012+A2: 2016
BS EN IEC 60598-1:2021
BS EN 62493:2015+A1:2022
BS EN IEC 62031:2020+A11:2021


130

ELECTRICAL

SOURCE TYPE PRODUCT CLASS DIMMING PROTOCOL


Ξ	LED
ŝ	Class III (SELV low voltage)
L	1-10V dimmable
	DALI dimmable
	Mains dimmable (phase cut dimming)
	Switched

COLOUR VECTOR GRAPHIC 8 70 Fidelit 80 ndex, F





FIRE RATED N/A



WWW.JOHNCULLENLIGHTING.COM

BRITISH

UK CA

 \cap



UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

© John Cullen Lighting 2024. Technical data figures are for guidance only and are subject to ±5% tolerance We reserve the right to change the design and specification of our product range without prior notice. E&OE

