PAGE 1 OF 2 30/04/2024 V1.47



## LUCCA 30 STEPLIGHT WIDE BRONZE WITH COWL 2024

SLL3TWG062

LUMINAIRE REF:


PROJECT REF:



BRONZE ANODISED

The new Lucca 30 is an energy efficient LED miniature steplight with a glare cowl incorporating new ProVent technology which minimises condensation and improves robustness. Built for the circular economy, the LED engine is now fully serviceable. It is ideal for creating stunning skimming light across steps. It comes with narrow, medium or wide beams to suit your projects. This product can also be used as a downlight.

It is IP67 rated so ideal for use both inside and out. Fittings come with 1m of cable as standard. Custom cable lengths are available upon request. If using inside, the warranty increases to 5 years.





WIDE

## **ACCESSORIES**



IP66 ENCLOSURE FOR DRIVER LARGE ACENIPLRG



IP66 ENCLOSURE FOR DRIVER SMALL



PAGE 2 OF 2 30/04/2024 V1.47




## LUCCA 30 STEPLIGHT WIDE BRONZE WITH COWL 2024

LUMINAIRE REF:
PROJECT REF:

SLL3TWG062

SPECIFICATION	350mA	500mA	700mA
BEAM ANGLE (°)	36°	36°	36°
LED SOURCE LUMENS (LM)	101	137	181
LUMINAIRE LUMENS (LM)	62	84	111
LUMINAIRE EFFICACY (LM/W)	62	56	53
INTENSITY RATING (CD)	154	212	282
POWER CONSUMPTION (W)	1	1.5	2.1
DRIVE CURRENT (mA)	350	500	700
FORWARD VOLTAGE (V DC)	3	3	3
MAX TEMPERATURE (°C)	40	40	35




TM66	2.4 (LIA Assured Verification Score)
INGRESS RATING	IP65 + IP67
IMPACT RATING	IK08
COMPLIANCE	BS EN 60598-2-13: 2006+A1: 2012+A2: 2016
	BS EN IEC 60598-1:2021
	BS EN 62493:2015+A1:2022
	BS EN IEC 62031:2020+A11:2021


COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	98 Ra
IES TM-30 COLOUR FIDELITY (Rf)	93.8
IES TM-30 COLOUR GAMUT (Rg)	98.1
BINNING	2 SDCM (Equivalent)
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	N/A

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	1-10V dimmable
	DALI dimmable
	Mains dimmable (phase cut dimming)
	6 201 1

OTHER DATA	
CABLE TYPE	2 Core Silicone (180°C)
CABLE SIZE	6mm OD - 2 off 24/0.2 (0.75mm2)
CABLE LENGTH	1000mm
CONNECTOR TYPE	N/A
WEIGHT	N/A
FIRE RATED	N/A

**TM66** 







WWW.JOHNCULLENLIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81