

## LUCCA 30 STEPLIGHT WIDE STAINLESS STEEL WITH COWL 2024 SLL3TWG172

LUMINAIRE REF:


PROJECT REF:



The new Lucca 30 is an energy efficient LED miniature steplight with a glare cowl incorporating new ProVent technology which minimises condensation and improves robustness. Built for the circular economy, the LED engine is now fully serviceable. It is ideal for creating stunning skimming light across steps. It comes with narrow, medium or wide beams to suit your projects. This product can also be used as a downlight.

It is IP67 rated so ideal for use both inside and out. Fittings come with 1m of cable as standard. Custom cable lengths are available upon request. If using inside, the warranty increases to 5 years.

#### STAINLESS STEEL





WIDE

### ACCESSORIES





FOR DRIVER LARGE ACENIPLRG IP66 ENCLOSURE FOR DRIVER SMALL ACENIPSML



WWW.JOHNCULLENLIGHTING.COM UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

# JOHN CI II I EN

700mA

36°

181

111

53

282

2.1

700

3

## LUCCA 30 STEPLIGHT WIDE STAINLESS STEEL WITH COWL 2024 SLL3TWG172

350mA

36°

101

62

62

154

350

500mA

36°

137

84

56


212

1.5

500

#### LUMINAIRE REF:

PROJECT REF:



2700K	COLOUR TEMPERATURE
98 Ra	CIE CRI AVAILABLE AS
93.8	IES TM-30 COLOUR FIDELITY (Rf)
98.1	IES TM-30 COLOUR GAMUT (Rg)
2 SDCM (Equi	BINNING
>50000	LIFETIME L70/B10 (HOURS)
N/A	AMBIENT TEMPERATURE (Ta)
	OTHER DATA

TEMPERATURE (Ta)	N/A
OTHER DATA	
CABLE TYPE	2 Core Silicone (180°C)
CABLE SIZE	6mm OD - 2 off 24/0.2 (0.75mm2)
CABLE LENGTH	1000mm
CONNECTOR TYPE	N/A
WEIGHT	N/A
FIRE RATED	N/A

ivalent

TM66	2.4 (LIA Assured Verification Score)	
ESS RATING	IP65 + IP67	
CT RATING	IK08	IES TM
OMPLIANCE	BS EN 60598-2-13: 2006+A1: 2012+A2: 2016	IES TN
	BS EN IEC 60598-1:2021	
	BS EN 62493:2015+A1:2022	L
	BS EN IEC 62031:2020+A11:2021	AM
LECTRICAL		
URCE TYPE	LED	
UCT CLASS	Class III (SELV low voltage)	
PROTOCOL	1-10V dimmable	

Mains dimmable (phase cut dimming)

Switched

INGRE IMPA

SPECIFICATION

BEAM ANGLE (°)

LED SOURCE LUMENS (LM)

LUMINAIRE LUMENS (LM)

INTENSITY RATING (CD)

DRIVE CURRENT (mA)

LUMINAIRE EFFICACY (LM/W)


POWER CONSUMPTION (W)

FORWARD VOLTAGE (V DC)


MAX TEMPERATURE (°C)

## E

SOL PROD DIMMING F DALI dimmable







## 3 WARRANTY

WWW.JOHNCULLENLIGHTING.COM UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

CISSI CISI CISSI C