


LUMINAIRE REF:

PROJECT REF:



The new Lucca 40 is an energy efficient LED midi uplight with a glare cowl incorporating new ProVent technology which minimises condensation and improves robustness. Built for the circular economy, the LED engine is now fully serviceable. It is ideal for creating stunning uplighting effects to columns, arches, window reveals and along walls. It comes with narrow, medium or wide beams to suit your projects. It is IP67 rated so ideal for use both inside and out. Fittings come with 1m of cable as standard. Custom cable lengths are available upon request. If using inside, the warranty increases to 5 years.

BLACK ANODISED





WIDE

ACCESSORIES



IP66 ENCLOSURE FOR DRIVER LARGE ACENIPLRG IP66 ENCLOSURE FOR DRIVER SMALL ACENIPSML

LUCCA 40 TRIM BURIAL SLEEVE ACL4TRS2



UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

© John Cullen Lighting 2024. Technical data figures are for guidance only and are subject to ±5% tolerance We reserve the right to change the design and specification of our product range without prior notice. E&OE



WWW.JOHNCULLENLIGHTING.COM

BRITISH DESIGN UK CA

 \cap

JOHN CUILLEN

700mA

39°

181

108

51

236

2.1

700

40

Cable Type

Cable Size Cable Length

Connector Typ Weight

Fire rated

LUCCA 40 WIDE BLACK WITH COWL 2024 ULL4TWG022

350mA

39°

101

60

60


131

350

40

LUMINAIRE REF:

PROJECT REF:



COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	98 Ra
IES TM-30 COLOUR FIDELITY (Rf)	94.8
IES TM-30 COLOUR GAMUT (Rg)	97.9
BINNING	2 SDCM (Equivalent)
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	N/A
OTHER DATA	
	2 Core Silicone (180°C)
	6mm OD - 2 off 24/0.2 (0.75mm2)
	1000mm
De	N/A

N/A N/A

TM66	2.4 (LIA Assured Verification Score)
INGRESS RATING	IP65 + IP67
IMPACT RATING	IK08
COMPLIANCE	BS EN 60598-2-13: 2006+A1: 2012+A2: 2016
	BS EN IEC 60598-1:2021
	BS EN 62493:2015+A1:2022
	BS EN IEC 62031:2020+A11:2021

500mA

39°

137

82

55

179

1.5

500

4C

ELECTRICAL

SOURCE TYPE PRODUCT CLASS DIMMING PROTOCOL

COLOUR VECTOR GRAPHIC

SPECIFICATION

BEAM ANGLE (°)

LED SOURCE LUMENS (LM)

LUMINAIRE LUMENS (LM)

INTENSITY RATING (CD)

DRIVE CURRENT (mA)

LUMINAIRE EFFICACY (LM/W)

POWER CONSUMPTION (W)

FORWARD VOLTAGE (V DC) MAX TEMPERATURE (°C)

LED
Class III (SELV low voltage)
DALI dimmable
1-10V dimmable
Mains dimmable (phase cut dimming)
Cultabad

		-	-	-	-	-	-		-	-	-		-								Gamut Index, R _g													
																			8		8		80		8		100	-	5	120		130		140
																			S T						-		+++							1
				-	/	-	T	-	-	-																								
			1	1							1								8															
			1				+			-									~ h	1													1.1	
												1						21	. 8															
			-				+											語り	5 -															
												1						Fidelity Index, R,	- 8												1			
			1									/						8	8				h. 1											
			1							12	/							20	1					1										
				-	-				_	/									8										1					
					1	-													° 1									1						
																			. 8								۰.							
		_							-										8 H	-	-	-	-	-	-		- 10	-	-	-	-	-	-	
		_	Refe	renc	e III	umir	ant			-	163	1 50	urce	50																				
	_																																	_
100																																		
					-11													_	_	_								-		а. 1				1
			ш						1		d,		H		LI	l I		l h					Ы			п			ы	Ы				
80			ш								L												ш											
0Ē			ш								L												ш							ш				
Fidelity Index, R ₄ 0			ш								L								ш				ш											
i i			ш								L								ш				ш											
di le			ш								L												ш							ш				
₩ 40			ш								L								ш				ш											
							П				T.																							
20	4						П				T.																							
							П				T.																							
							П				T.																							
0	CESO1	CES OF	ctso?	CIS11	CES13	005.15	CES III	ct521	CES 23	CIS 25	17 (2)	ctsh	ctsan 1	CUS IS	crsan	CES41	CE543	CES47	CISA)	crsss	CESS?	cesso .	CES61	CE565	CLS40	dts71	CES 72	CC570	cusan a	(CS 22)	CIS87	COM .	CCS 8	cts#
	22	2 2	2	CIS11	1.12	00515	0 2	2	22	20.1	ő ż	5 22	2	20	5 2	2	21 3	2 22	10 2	5 22	22 23	22	3 3	12	6 2	2 3	2 23	2 2	3	2 2	2 2	12 2	2 2	CES97 CES99
	8	0.0		9.9		0.1			0	0.1	9.9	2.0	0	0.4	5 0				0.0		0.0	0	0.0	0	0.0	0.4	10	0.0	0.	0.0	0 0	0.0	0.0	0.0



Colour Rendering Index 120 80 Values 60
 R1
 R2
 R3
 R4
 R5
 R6
 R7

 98
 99
 94
 96
 99
 100
 98
93 99 95 91



WWW.JOHNCULLENLIGHTING.COM UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

© John Cullen Lighting 2024. Technical data figures are for guidance only and are subject to ±5% tolerance We reserve the right to change the design and specification of our product range without prior notice. E&OE



UK CA

 \mathbb{C}

BRITISH DESIGN