PAGE 1 OF 2 17/04/2024 V1.43



LUCCA 40 ASYMMETRIC BRASS 2024

ULL4TA042

LUMINAIRE REF:

PROJECT REF:



BRASS

The new Lucca 40 is an energy efficient LED midi uplight incorporating new ProVent technology which minimises condensation and improves robustness. Built for the circular economy, the LED engine is now fully serviceable. It is ideal for creating stunning uplighting effects to columns, arches, window reveals and along walls. It is IP67 rated so ideal for use both inside and out. Fittings come with 1m of cable as standard. Custom cable lengths are available upon request. If using inside, the warranty increases to 5 years.





ASYMMETRIC

ACCESSORIES



IP66 ENCLOSURE FOR DRIVER LARGE

ACENIPLRG



IP66 ENCLOSURE FOR DRIVER SMALL ACENIPSML



ACL4TRS2



WWW.JOHNCULLENLIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81











PAGE 2 OF 2 17/04/2024 V1.43



LUCCA 40 ASYMMETRIC BRASS 2024 ULL4TA042

LUMINAIRE REF:

PROJECT REF:


SPECIFICATION	350mA	500mA	700mA
BEAM ANGLE (°)	Asymmetric	Asymmetric	Asymmetric
LED SOURCE LUMENS (LM)	101	137	181
LUMINAIRE LUMENS (LM)	32	44	59
LUMINAIRE EFFICACY (LM/W)	32	29	28
INTENSITY RATING (CD)	138	205	271
POWER CONSUMPTION (W)	1	1.5	2.1
DRIVE CURRENT (mA)	350	500	700
FORMULARD VIOLENCE AVEC	0	0	^


TM66	2.4 (LIA Assured Verification Score)
INGRESS RATING	IP65 + IP67
IMPACT RATING	IK08
COMPLIANCE	BS EN 60598-2-13: 2006+A1: 2012+A2: 2016
	BS EN IEC 60598-1:2021
	BS EN 62493:2015+A1:2022
	BS EN IEC 62031:2020+A11:2021

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	DALI/Phase cut/1-10V/Dimmable1-10V dimmable

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	98 Ra
IES TM-30 COLOUR FIDELITY (Rf)	94.5
IES TM-30 COLOUR GAMUT (Rg)	97.6
BINNING	2 SDCM (Equivalent)
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	N/A

	OTHER DATA	
Cable Type		2 Core Silicone (180°C)
Cable Size		6mm OD - 2 off 24/0.2 (0.75mm2)
Cable Length		1000mm
Connector Type		N/A
Weight		N/A
Fire rated		N/A







WWW.JOHNCULLENLIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81







