

LUCCA 40 TRIMLESS WIDE BLACK WITH COWL
2024
ULL4FWG022

LUMINAIRE REF:



PROJECT REF:



BLACK ANODISED


The new Lucca 40 is a trimless energy efficient LED midi uplight incorporating new ProVent technology which minimises condensation and improves robustness. Built for the circular economy, the LED engine is now fully serviceable. It is ideal for creating stunning uplighting effects to columns, arches, window reveals and along walls. It comes with narrow, medium, wide, elliptical and asymmetric beams to suit your projects.

It is IP67 rated so ideal for use both inside and out. Fittings come with a burial sleeve and 1m of cable as standard. Custom cable lengths are available upon request. If using inside, the warranty increases to 5 years.




WIDE

ACCESSORIES



IP66 ENCLOSURE
FOR DRIVER
LARGE
ACENIPLRG



IP66 ENCLOSURE
FOR DRIVER
SMALL
ACENIPSML



LUCCA 40 TRIMLESS WIDE BLACK WITH COWL


2024

ULL4FWG022

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	350mA	500mA	700mA
BEAM ANGLE (°)	39°	39°	39°
LED SOURCE LUMENS (LM)	101	137	181
LUMINAIRE LUMENS (LM)	60	82	108
LUMINAIRE EFFICACY (LM/W)	60	55	51
INTENSITY RATING (CD)	131	179	236
POWER CONSUMPTION (W)	1	1.5	2.1
DRIVE CURRENT (mA)	350	500	700
FORWARD VOLTAGE (V DC)	3	3	3
MAX TEMPERATURE (°C)	40	40	40



TM66	2.4 (LIA Assured Verification Score)
INGRESS RATING	IP65 + IP67
IMPACT RATING	IK08
COMPLIANCE	BS EN 60598-2-13: 2006+A1: 2012+A2: 2016
	BS EN IEC 60598-1:2021
	BS EN 62493:2015+A1:2022
	BS EN IEC 62031:2020+A11:2021

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	98 Ra
IES TM-30 COLOUR FIDELITY (Rf)	94.8
IES TM-30 COLOUR GAMUT (Rg)	97.9
BINNING	2 SDCM (Equivalent)
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	N/A

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	DALI/Phase cut/1-10V/Dimmable1-10V dimmable

OTHER DATA	
CABLE TYPE	2 Core Silicone (180°C)
CABLE SIZE	6mm OD - 2 off 24/0.2 (0.75mm ²)
CABLE LENGTH	1000mm
CONNECTOR TYPE	N/A
WEIGHT	N/A
FIRE RATED	N/A

