PAGE 1 OF 2 30/04/2024 V1.25



VORSA FIX 50 SUPER SPOT BLACK 2024

SLVF5SS025


LUMINAIRE REF:

PROJECT REF:



BLACK RAL 9005

The new Vorsa Fix 50 spotlight is a surface-mounted directional spotlight. It has been re-engineered for 2024 with a cleaner aesthetic, an increased light output and an industry-leading light output at 98 CRI. Interchangeable optics allow for a range of beam distributions, all easy to fit on-site. We have introduced a new innovative screwless selfsupporting tilt mechanism. It is perfect for use on beams and concrete ceilings where recessed fittings are unsuitable. This small spotlight is discreet and easy to direct the light where required. The fitting has a deep baffle which ensures that glare is minimised. The range has been built to the principles of the circular economy to not only maximise resources but also to reduce waste and environmental impact.



ACCESSORIES



VORSA 50 HONEYCOMB INSERT Ø48MM X 3ММ ACHCVO502



VORSA 50 SAND BLASTED GLASS INSERT Ø48MM X 3ММ

ACSGVO502



VORSA 50 HIGH TRANSMISSION SOFTENING GLASS INSERT Ø48MM X 3ММ ACSLVO502



WWW.JOHNCULLENLIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81







PAGE 2 OF 2 30/04/2024 V1.25



VORSA FIX 50 SUPER SPOT BLACK 2024 SLVF5SS025

LUMINAIRE REF:

PROJECT REF:


SPECIFICATION	SUPER SPOT
BEAM ANGLE (°)	11°
LED SOURCE LUMENS (LM)	486
LUMINAIRE LUMENS (LM)	410
INTENSITY RATING (CD)	6440
POWER CONSUMPTION (W)	6
LUMINAIRE EFFICACY (LM/W)	68
DRIVE CURRENT (mA)	350
FORWARD VOLTAGE (V DC)	N/A


IM66	2.3 (LIA Assured Verification Score)
INGRESS RATING	IP20
IMPACT RATING	IK03
COMPLIANCE	IEC 60598-1:2020
	IEC 60598-2-1:2020

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	>95 Ra
IES TM-30 COLOUR FIDELITY (Rf)	>95
IES TM-30 COLOUR GAMUT (Rg)	≈100
BINNING	2-step
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 +25 °C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	0-10V dimmable
	DALI dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	FEP (200 °C)
CABLE SIZE	2 off 22AWG 19/0.15 (0.15mm2)
CABLE LENGTH	150
CONNECTOR TYPE	Leads included
WEIGHT	380
FIRE RATED	N/A





5 WARRANTY WWW.JOHNCULLENLIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81





