

VORSA PORT 40 SPOT BLACK 2024
SLVP4S025


LUMINAIRE REF:

PROJECT REF:



WHITE RAL 9003

The new Vorsa Port 40 spotlight has been re-imagined as a simplified mini plaster-in spotlight. It has been re-engineered for 2024 with a cleaner aesthetic, an increased light output and an industry-leading light output at 98 CRI. Interchangeable optics allow for a range of beam distributions, all easy to fit on-site. We have introduced a new innovative screwless self-supporting tilt mechanism. It comes complete with recyclable cardboard protection shield for first fix installation. The range has been built to the principles of the circular economy to not only maximise resources but also to reduce waste and environmental impact.



ACCESSORIES

				
VORSA 40 HONEYCOMB INSERT Ø33MM X 3MM ACHCVO402	VORSA 40 SAND BLASTED GLASS INSERT Ø33MM X 3MM ACSGVO402	VORSA 40 HIGH TRANSMISSION SOFTENING GLASS INSERT Ø33MM X 3MM ACSLVO402	VORSA PORT PLASTER IN FRAME WHITE RAL 9003 SLVPXX015-Frame	VORSA PORT PLASTER IN FRAME BLACK RAL 9003 SLVPXX025-Frame



VORSA PORT 40 SPOT BLACK 2024
SLVP4S025

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	SPOT
BEAM ANGLE (°)	9°
LED SOURCE LUMENS (LM)	486
LUMINAIRE LUMENS (LM)	225
INTENSITY RATING (CD)	3990
POWER CONSUMPTION (W)	6
LUMINAIRE EFFICACY (LM/W)	38
DRIVE CURRENT (mA)	350
FORWARD VOLTAGE (V DC)	18.5

TM66	2.3 (LIA Assured Verification Score)
INGRESS RATING	IP20
IMPACT RATING	IK03
COMPLIANCE	IEC/EN 60598-1:2021
	IEC 60598-2-2:2011

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	>95 Ra
IES TM-30 COLOUR FIDELITY (Rf)	>95
IES TM-30 COLOUR GAMUT (Rg)	≈100
BINNING	2-step
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 ... +25 °C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	0-10V dimmable
	DALI dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
Cable Type	FEP (200 °C)
Cable Size	2 off 22AWG 19/0.15 (0.15mm2)
Cable Length	150
Connector Type	Leads included
Weight	320
Fire rated	N/A

