

## CONTOUR HORIZONTAL 10W IP67 FLEXI HORIZONTAL BEND LED STRIP

LUMINAIRE REF:

PROJECT REF:

 $\int O$ 

The Contour Horizontal is a 10W bendy LED strip emitting light horizontally to the side to provide detail lighting. It can be used to highlight features of joinery, stair treads or illuminate shelving where a bend is required of up to 100mm diameter.

This product is made to order to precise measurements. It has a front cable entry (IP44) or an IP67 side and bottom cable entries. If using inside, the warranty increases to 5 years.

N/A



WWW.JOHNCULLENLIGHTING.COM UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

© John Cullen Lighting 2024. Technical data figures are for guidance only and are subject to ±5% tolerance We reserve the right to change the design and specification of our product range without prior notice. E&OE





## CONTOUR HORIZONTAL 10W IP67 FLEXI HORIZONTAL BEND LED STRIP

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	LAMBERTIAN		
BEAM ANGLE (°)	120°		
LED SOURCE LUMENS (LM)	560		
LUMINAIRE LUMENS (LM)	560		
INTENSITY RATING (CD)	N/A		
POWER CONSUMPTION (W)	10W		
LUMINAIRE EFFICACY (LM/W)	56		
DRIVE CURRENT (mA)	24vDC		
FORWARD VOLTAGE (V DC)	N/A		
INGRESS RATING		COLOUR TEMPERATURE	
IMPACT RATING	N/A	CIE CRI AVAILABLE AS	
COMPLIANCE		IES TM-30 COLOUR FIDELITY (Rf)	N/A
		IES TM-30 COLOUR GAMUT (Rg)	N/A
		BINNING	2 SDCM
		LIFETIME L70/B10 (HOURS)	>50000
		AMBIENT TEMPERATURE (Ta)	-25 +65°C
ELECTRICAL		OTHER DATA	
SOURCE TYPE			8 Core Silicone (180 °C)
PRODUCT CLASS		CABLE SIZE	
DIMMING PROTOCOL			Length to order
	DALI dimmable	CONNECTOR TYPE	
	Mains dimmable (phase cut dimming)	WEIGHT	
	Switched	FIRE RATED	N/A



WWW.JOHNCULLENLIGHTING.COM UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

 $\odot$  John Cullen Lighting 2024. Technical data figures are for guidance only and are subject to ±5% tolerance We reserve the right to change the design and specification of our product range without prior notice. E&OE CE