

## CONTOUR MINI TWIST 10W 2400K IP67 LICN1010TW24IP67

LUMINAIRE REF:


PROJECT REF:



The Contour Mini Twist is a 10W IP rated flexible and twistable LED strip that twists on both axis. It can be used to highlight features of spiral features such as staircases and handrails where a twist is required.

This product is made to order to precise measurements. It has a front cable entry, side or bottom cable entries.







WWW.JOHNCULLENLIGHTING.COM UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

© John Cullen Lighting 2024. Technical data figures are for guidance only and are subject to ±5% tolerance We reserve the right to change the design and specification of our product range without prior notice. E&OE



LICN1010TW24IP67



CONTOUR MINI TWIST 10W 2400K IP67

LUMINAIRE REF:

PROJECT REF:

## SPECIFICATION LAMBERTIAN BEAM ANGLE (°) 120° LED SOURCE LUMENS (LM) 398 LUMINAIRE LUMENS (LM) 398 INTENSITY RATING (CD) N/A POWER CONSUMPTION (W) 10W LUMINAIRE EFFICACY (LM/W) 39.8 DRIVE CURRENT (mA) 24vDC FORWARD VOLTAGE (V DC) N/A INGRESS RATING IP67 COLOUR TEMPERATURE 2400K IMPACT RATING N/A CIE CRI AVAILABLE AS >90 Ra IES TM-30 COLOUR FIDELITY (Rf) N/A COMPLIANCE IES TM-30 COLOUR GAMUT (Rg) N/A BINNING 2 SDCM LIFETIME L70/B10 (HOURS) >50000 AMBIENT TEMPERATURE (Ta) -25 ... +65°C ELECTRICAL OTHER DATA SOURCE TYPE LED CABLE TYPE 2 Core Silicone (180 °C) PRODUCT CLASS CABLE SIZE N/A N/A DIMMING PROTOCOL CABLE LENGTH 1-10V dimmable Length to orde DALI dimmable CONNECTOR TYPE N/A Mains dimmable (phase cut dimming) WEIGHT N/A Switched FIRE RATED N/A



WWW.JOHNCULLENLIGHTING.COM UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

@ John Cullen Lighting 2024. Technical data figures are for guidance only and are subject to  $\pm 5\%$  tolerance We reserve the right to change the design and specification of our product range without prior notice. E&OE