PAGE 1 OF 2 14/05/2024 V1.22



## **CONTOUR MINI TWIST 10W 2700K IP67**

LICN1010TW27IP67


LUMINAIRE REF:

PROJECT REF:



The Contour Mini Twist is a 10W IP rated flexible and twistable LED strip that twists on both axis. It can be used to highlight features of spiral features such as staircases and handrails where a twist is required.

This product is made to order to precise measurements. It has a front cable entry, side or bottom cable entries. If using inside, the warranty increases to 5 years.





WWW.JOHNCULLENLIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

PAGE 2 OF 2 14/05/2024 V1.22



## **CONTOUR MINI TWIST 10W 2700K IP67**

LICN1010TW27IP67

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	LAMBERTIAN
BEAM ANGLE (°)	120°
LED SOURCE LUMENS (LM)	409
LUMINAIRE LUMENS (LM)	409
INTENSITY RATING (CD)	N/A
POWER CONSUMPTION (W)	10W
LUMINAIRE EFFICACY (LM/W)	47.8
DRIVE CURRENT (mA)	24vDC
FORWARD VOLTAGE (V DC)	N/A

INGRESS RATING	IP67
IMPACT RATING	N/A
COMPLIANCE	

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	>90 Ra
IES TM-30 COLOUR FIDELITY (Rf)	N/A
IES TM-30 COLOUR GAMUT (Rg)	N/A
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-25 +65°C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	N/A
DIMMING PROTOCOL	1-10V dimmable
	DALI dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	3 Core Silicone (180 °C)
CABLE SIZE	N/A
CABLE LENGTH	Length to order
CONNECTOR TYPE	N/A
WEIGHT	N/A
FIRE RATED	N/A



WWW.JOHNCULLENLIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

