PAGE 1 OF 2 14/05/2024 V1.21



CONTOUR VERTICAL 15W 2400K IP67

LICN1615VB24IP67

LUMINAIRE REF:


PROJECT REF:



The Contour Vertical is a 15W bendy LED strip emitting light on the top of the curve to provide detail lighting. It can be used to highlight features of joinery, stair treads or illuminate shelving where a bend is required of up to 240mm diameter.

This product is made to order to precise measurements. It has a front, side or bottom cable entries. If using inside, the warranty increases to 5 years.

N/A





WWW.JOHNCULLENLIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

PAGE 2 OF 2 14/05/2024 V1.21



CONTOUR VERTICAL 15W 2400K IP67

LICN1615VB24IP67

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	LAMBERTIAN
BEAM ANGLE (°)	120°
LED SOURCE LUMENS (LM)	470
LUMINAIRE LUMENS (LM)	470
INTENSITY RATING (CD)	N/A
POWER CONSUMPTION (W)	10W
LUMINAIRE EFFICACY (LM/W)	47
DRIVE CURRENT (mA)	24vDC
FORWARD VOLTAGE (V DC)	N/A

INGRESS RATING	IP67
IMPACT RATING	N/A
COMPLIANCE	

COLOUR TEMPERATURE	2400K
CIE CRI AVAILABLE AS	>90 Ra
IES TM-30 COLOUR FIDELITY (Rf)	N/A
IES TM-30 COLOUR GAMUT (Rg)	N/A
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-25 +60°C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	N/A
DIMMING PROTOCOL	1-10V dimmable
	DALI dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	10 Core Silicone (180 °C)
CABLE SIZE	N/A
CABLE LENGTH	Length to order
CONNECTOR TYPE	N/A
WEIGHT	N/A
FIRE RATED	N/A



WWW.JOHNCULLENLIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

