PAGE 1 OF 2 14/05/2024 V1.20



CONTOUR HORIZONTAL 15W 2700K IP67

LICN1615HB27IP67

LUMINAIRE REF:


PROJECT REF:



N/A

The Contour Horizontal is a 15W bendy LED strip emitting light horizontally to the side to provide detail lighting. It can be used to highlight features of joinery, stair treads or illuminate shelving where a bend is required of up to 240mm diameter.

This product is made to order to precise measurements. It has a front, side or bottom cable entries.





WWW.JOHNCULLENLIGHTING.COM

 $\mathsf{UK} + 44 \ (0) \ 20 \ 7371 \ 9000 \ | \ \mathsf{Middle} \ \mathsf{East} \ \& \ \mathsf{APAC} + 971 \ (0) \ 4 \ 321 \ 114 \ | \ \mathsf{Europe} \ + 33 \ (0) 9 \ 61 \ 68 \ 22 \ 81 \ | \ \mathsf{APAC} + 971 \ (0) \ \mathsf{APAC} + 971 \ \mathsf{APA$

PAGE 2 OF 2 14/05/2024 V1.20



CONTOUR HORIZONTAL 15W 2700K IP67

LICN1615HB27IP67

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	LAMBERTIAN
BEAM ANGLE (°)	120°
LED SOURCE LUMENS (LM)	942
LUMINAIRE LUMENS (LM)	942
INTENSITY RATING (CD)	N/A
POWER CONSUMPTION (W)	15W
LUMINAIRE EFFICACY (LM/W)	70
DRIVE CURRENT (mA)	24vDC
FORWARD VOLTAGE (V DC)	N/A

INGRESS RATING	IP67
IMPACT RATING	N/A
COMPLIANCE	

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	>90 Ra
IES TM-30 COLOUR FIDELITY (Rf)	N/A
IES TM-30 COLOUR GAMUT (Rg)	N/A
BINNING	2SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-25 +60°C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	N/A
DIMMING PROTOCOL	1-10V dimmable
	DALI dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	13 Core Silicone (180 °C)
CABLE SIZE	N/A
CABLE LENGTH	Length to order
CONNECTOR TYPE	N/A
WEIGHT	N/A
FIRE RATED	N/A



WWW.JOHNCULLENLIGHTING.COM

UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114 | Europe +33 (0)9 61 68 22 81

